

1568 First Street North
Alabaster, AL 35007

(800) 633-3415
www.specrubber.com

SRP NSF-61 Sheet Packing Product Specification Sheet

MATERIAL PROPERTIES¹

Color:	Black
Composition:	EPDM Elastomer sulfur cure
Hardness, Shore A, +/-5:	75
Temperature rating ² , °F (°C)	
Minimum:	-20(-29)
Maximum:	+250(+122)
Pressure ² , Maximum psig (bar):	175(12)
Finish available	Smooth
Thickness ³	1/16" 1/8", 1/4", 1/2"
Standard Width ³	48"
Additional With ³	36", 72"
Standard Roll Length ⁴	1/16"-50 ft 1/8"-50 ft 1/4"-30 ft 1/2"-30 ft
Certification:	NSF-61
Specification:	ANSI/AWWA C111/A21.11
Custom lengths available upon request	

PHYSICAL PROPERTIES¹

ASTM D412	Tensile Strength, psi (N/mm ²):	
ASTM D412	Elongation %:	1500 (10.4)
ASTM D395B	Compression Set, 25% Deflection, Max. % 22 hours at 158°F (70°C):	150 20
ASTM D2000	Line Call Out:	3BA715A14B13C12Z1-75+/-5

Note: These are general guidelines and should not be the sole means to qualify product

¹Values do not express specific limits

²When using products at maximum or minimum limits please consult Specification Rubber Products with specific application

³Minimum runs may apply

⁴Standard roll lengths +/- 10%



**Underwriters
Laboratories**