


# Specification Rubber Products, Inc.

1568 1st St N  
Alabaster, AL 35007  
800-633-3415  
[specrubber.com](http://specrubber.com)


## BARRACUDA® RJ GASKETS

- Available in 4" - 16"
- Available in NSF-61 certified SBR, EPDM, Nitrile, and FKM
- Neoprene also available
- Safety orange color gives visual confirmation restrained joint gasket is installed properly
- Licensed TYTON® Gasket Manufacturer




## FILLER FLANGE GASKETS

- Full Face and Ring Style
- NSF-61 certified EPDM
- Offered in 1/16", 1/8", 1/4" and 1/2" thicknesses
- 250 PSI rated working pressure
- Up to three gaskets can be stacked to fill 1-1/2" space



## EPDM SHEET RUBBER

- NSF-61 certified EPDM
- Offered in 1/16", 1/8", 1/4" and 1/2" thicknesses
- Sold by the Roll or Linear Foot
- Made in the USA
- "EPDM NSF-61 Made in USA" branding for easy identification



## TYTON® PUSH-ON GASKETS

- Available in 3" - 48"
- Available in NSF-61 certified SBR, EPDM, Nitrile, and FKM
- Neoprene also available
- Licensed TYTON® Gasket Manufacturer



## FLANGE ACCESSORY KITS

- 2" - 64" available upon request
- Domestic and Import
- Aluminum, Stainless Steel and Zinc coatings available
- For other options, please call for more info



## TORUSEAL® FLANGE GASKETS

- Available in 2" - 64"
- 1/8" thickness
- 250-300 PSI rated working pressure
- Available in NSF-61 certified SBR, EPDM, Nitrile, and FKM
- Neoprene also available
- Dual-bulb design provides positive sealing for ductile iron flanged piping



## METERSEAL™ GASKETS

- MeterSeal™ tabbed and oval available in both 1-1/2" & 2" diameters
- 200 PSI rated working pressure
- Molded bulb on ID improves sealing with mismatched faces and uneven torque on bolts
- Available in NSF-61 certified SBR, EPDM, Nitrile, and FKM



## FLAT METER GASKETS

- Tabbed and oval available in both 1- 1/2" & 2" diameters
- NSF-61 certified EPDM
- 150 PSI rated working pressure
- Oval style offered in 1/16", 1/8", 1/4" and 1/2"
- Tabbed style offered in 1/16", 1/8" and 1/4" thicknesses



## MJ GASKETS


- Stocked in 3" - 48"
- Larger sizes available upon request
- Available in NSF-61 certified SBR, EPDM, Nitrile, and FKM
- Neoprene also available



## MJ TRANSITION GASKETS

- Stocked in 2" - 12"
- Larger sizes available upon request
- Available in NSF-61 certified SBR, EPDM, Nitrile and FKM
- Neoprene also available





# Specification Rubber Products, Inc.

1568 1st St N  
Alabaster, AL 35007  
800-633-3415  
[specrubber.com](http://specrubber.com)



Since 1968, Specification Rubber Products has manufactured gaskets and sealing solutions for the waterworks industry in our state-of-the-art facility in Alabaster, Alabama. Our qualified and experienced technical staff is available to provide knowledgeable insight and advice based on over 55 years of industry experience. Our dynamic and adaptive sales and customer service team is always ready to provide the highest level of care so that you can, in turn, provide your customers with the best gaskets and sealing solutions made in the USA. Give us a call to see why our customers choose Specification Rubber Products and learn more about our full line of domestic, ANSI/AWWA C1.11/A21.11, NSF-61 certified, UL-listed gaskets and sealing solutions. Our number one goal is to meet or exceed our customers' expectations every time. For inquiries, quotes, or orders, please call 800-633-3415 or email us at [specificationrubber@specrubber.com](mailto:specificationrubber@specrubber.com).



## Available Elastomers

### SBR

- Suitable for fresh water, salt water, sanitary sewage, and greasy water
- Temperature rating is up to 150 F

### EPDM

- Suitable for fresh water, salt water, storm water, sanitary sewage, vegetable oil, elevated temperatures, dilute acids, dilute alkalis, ketones, and alcohol
- Temperature rating up to 212 F

### NBR

- Suitable for fresh water, salt water, storm water, sanitary sewage, refined petroleum oils and fluids, fats and greases
- Nitrile is resistant to deterioration, but impermeable to low molecular weight petroleum products
- Temperature rating up to 150 F

### NEOPRENE

- Suitable for fresh water, salt water, storm water, sanitary sewage and greasy water
- Temperature rating up to 212 F

### FKM

- Commonly referred to as Viton® Suitable for fresh water, salt water, storm water, sanitary sewage, most chemicals and solvents, aromatic hydrocarbons and fuels and high temperatures
- FKM is specified for potable water lines in areas saturated with low molecular weight petroleum products
- Temperature rating up to 300 F

