



# Barracuda® Gaskets

## Submittal Sheet

1568 First Street North  
Alabaster, AL 35007

(800) 633-3415  
[www.specrubber.com](http://www.specrubber.com)

- Specification Rubber's Barracuda® Gaskets instantly restrain ductile iron pipe, valves, and fittings having the TYTON® Joint.<sup>1</sup>
- Barracuda® Gaskets are suitable for water, wastewater, and other related applications.
- Barracuda® Gaskets are available with EPDM, SBR, Nitrile and FKM molded in **SAFETY ORANGE**. Neoprene are molded in black.
- Barracuda® Gaskets, when properly installed according to Specification Rubber's Assembly Instructions<sup>2</sup>, are rated up to 350 PSI and fully warranted by Specification Rubber Products.
- Gaskets available in 4" - 16".
- Barracuda® Gaskets, once properly installed, can be deflected up to 5°.
- Barracuda® Gaskets are manufactured in accordance with ANSI/AWWA C111/ A21.11 Rubber Gasket Joints for Ductile Iron Pressure Pipe and Fittings.
- All gaskets, except neoprene, are NSF-61 certified.
- All gaskets are manufactured in the U.S.A.

1- Tyton Joint® and Tyton® are registered trademarks and properties of United States Pipe and Foundry Company, LLC (U.S. Pipe). Neither Barracuda® nor Specification Rubber Products are affiliated with U.S. Pipe.

2- Assembly Instructions are provided with each Barracuda® Gasket.



**Underwriters  
Laboratories**

