



Specification
Rubber
Products, Inc.

NSF- 61 EPDM Sheet Material

Recommended for drinking water
applications/requirements

- NSF-61 Certified
- Formulated to meet or exceed ANSI/AWWA C111/A21.11 compound requirements
- EPDM Elastomer sulfur cured 75 Shore A Black, Smooth Finished
- Branded “EPDM NSF-61 Made in USA” for ease of identification
- Sold by the linear foot or in roll lengths
- Stocked and ready for immediate shipment
- Produced in the USA under a stringent ISO quality system



Technical Data	
Durometer	75 +/- 5
Temperature	-20° F to 250° F
Color/Finish	Black/ Smooth
Tensile Strength	1500
Elongation %	150

Width**	Gauge**	Part Number	Ln. Ft./Roll*	Sq. Yds./Roll	Approx. Lbs./Roll
48"	1/16"	790B-47501-124	50'	22.2	75
	1/8"	790B-47501-126	50'	22.2	155
	1/4"	790B-47501-127	15'	6.6	92
	1/2"	790B-47501-128	15'	6.6	181

*- sold by the foot

**- 36" and 72" widths available in 1/16" or 1/8" Special order– minimums apply



1568 First Street North

Alabaster, AL 35007

(800) 633-3415

www.specrubber.com