



**NSF-61 EPDM FULL-FACE FLANGE GASKET
VS. TRADITIONAL RED RUBBER FULL FACE
FLANGE GASKET, 1/8" THICKNESS**

P.O. BOX 568 ALABASTER, AL ISO 9001 CERTIFIED PHONE: 800-633-3415 WWW.SPECRUBBER.COM

		Specifications per AWWA C111	Spec Rubber's NSF- 61 EPDM 1/8" Full Face Flat Gasket*	Traditional Red Rubber 1/8" Full Face Flat Gasket
ASTM D412	Tensile	1500	1558	406
ASTM D412	Elongation	150	256	453
ASTM D412	Hardness	75 (+/- 5)	73	75
ASTM B395 B	Compression Set: 22 hours @ 158° F max %	20%	15%	43%
ASTM D573	Heat Age: 70 hours @ 212° F			
	Change Tensile	60%	+2.1	-5.4
	Change Elongation %	60%	-13.6	-9.1
	Hardness Change Points	N/A	+1	+5
ASTM D1149	Ozone: 70 hours @ 50 pphm @ 40° C	No Cracks	No Cracks Detected - PASS	Cracks Detected - FAIL
NSF-61 CERTIFIED			YES	NO
MADE IN THE USA			YES	NO

*Gaskets die cut from Specification Rubber's NSF-61 certified EPDM sheet material.