



1968-2018

Specification Rubber Products EPDM Filler Flange Gaskets



PRODUCT FEATURES

- Rated at 250 PSI for 12" and smaller
- Compatible with flanges conforming to AWWA C110, AWWA C115, and ASME B16.1 Class 125
- Saves time and money over traditional methods
- Installs as easily as any full-face or ring style flat gasket
- NSF-61 Certified
- High-quality EPDM rubber
- Stocked in 4"-12" in 1/2" and 1/4" thickness (other gasket sizes available by special order)
- Gaskets can be layered up to three plies, not to exceed 1 1/2"

Pipe Size (in.)	Pressure Rating* (PSI)	Recommended Bolt Torque** up to three plies (ft.-lbs.)
4	250	60
6	250	80
8	250	80
10	250	150
12	250	150

* Pressure rating designated is maximum water working pressure

Specification Rubber Products EPDM Filler Flange Gaskets are an alternative to the metal filler flanges. The EPDM Filler Flange gaskets are die cut from 1/4" or 1/2" thick NSF-61 certified EPDM rubber. The Filler Flange gaskets can be stacked up to 3 filler flange gaskets at any one fitting and are designed for use with standard flange bolts.

Specification Rubber Products EPDM Filler Flange Gaskets are manufactured in the USA under strict quality control procedures governed by ISO 9001:2008. Ensuring they meet or exceed requirements for use.

Certifications: NSF-61, ISO 9001:2008 Specification: ANSI/AWWA C111/A21.11



made
in the
USA



Underwriters
Laboratories