



**Specification  
Rubber  
Products, Inc.**

# EPDM SHEET RUBBER MATERIAL

## PRODUCT FEATURES

- NSF-61 Certified
- Formulated to meet or exceed ANSI/AWWA C111/A21.11 compound requirements
- EPDM Elastomer sulfur cured 75 Shore A Black, Smooth Finished
- Branded "EPDM NSF-61 Made in USA" for ease of identification
- 1/16", 1/8", 1/4" and 1/2" thicknesses available
- Sold by the roll or linear foot
- Stocked and ready for immediate shipment
- Produced in the USA under a stringent ISO quality system



Width**	Gauge**	Part Number	Ln.Ft./Roll*	Sq. Yds./Roll	Approx. Lbs./Roll
48"	1/16"	790B-47501-124	50'	22.2	75
	1/8"	790B-47501-126	50'	22.2	155
	1/4"	790B-47501-127	30'	6.6	92
	1/2"	790B-47501-128	30'	6.6	181

\*- sold by the foot

\*\* - 36" and 72" widths available in 1/16" or 1/8" Special order - minimums apply

Technical Data	
Durometer	75 +/- 5
Temperature	-20° F to 250° F
Color/Finish	Black/ Smooth
Tensile Strength	1500
Elongation %	150



## EPDM SHEET MATERIAL

- NSF-61 Certified • Made in the USA
- 1/16", 1/8", 1/4" and 1/2" thicknesses available • Sold by the roll or linear foot



[www.specrubber.com](http://www.specrubber.com)



**Underwriters  
Laboratories**

1568 1st St. N.  
Alabaster, AL 35007  
[www.specrubber.com](http://www.specrubber.com)

p: 800.633.3415  
f: 800.344.2031  
[info@specrubber.com](mailto:info@specrubber.com)